## NSN 4810-00-570-9195

Butterfly Valve - Page 1 of 1

A046b0



٧

| View Online at https://aerobasegroup.com/nsn/4810-00-570-9195  |
|--|
| Current Rating In Amps:  |
| 1.600  |
| Valve Operation Method:  |
| Electric motor   |
| Flange Shape:  |
| Round 1st end  |
| Connection Type:   |
| Flange 1st end   |
| Mounting Facility:   |
| Lug  |
| Power Drive Operating Pressure:  |
| 20.0 pounds per square inch  |
| Voltage In Volts And Current Type:   |
| 26.0 dc  |
| Outside Diameter:  |
| 5.061 inches 1st end   |
| Face To Face Distance:   |
| 4.375 inches   |
| Thickness:   |
| 0.156 inches 1st end   |
| Flange Face Design:  |
| Plain 1st end  |
| Special Features:  |
| One each airesearch rotary actuator part no 541090-5-1 installed.O/a dim, 9.50 inch lg by 5.56 inch w by 6.75 inch h                           |
| Material:  |
| Steel stem   |
| Surface Treatment:   |
| Passivate  |
| Style Designator:  |
| Straight thru  |
| Test Data Document:  |
| 81205-bac10-60495-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 99193-321674-3-1         |
| drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any        |
| specification, standard or other document that may be referenced in a basic governing drawing)   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |