## NSN 4810-00-578-0188

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-578-0188 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.625 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:** 0.091 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Power Drive Operating Pressure:** 5.0 pounds per square inch **Inlet/outlet Operating Pressure Differential:** 100.0 pounds per square inch **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 0.375 inches all ends **Voltage In Volts And Current Type:** 120.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device **Style Designator:** Straight thru **Thread Series Designator:** Npt all ends

N/a

Shelf Life:

## NSN 4810-00-578-0188

Solenoid Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0