

View Online at <https://aerobasegroup.com/nsn/4810-00-585-7135>

Bolt Hole Quantity:

12 1st end

Maximum Operating Temp:

200.0 degrees fahrenheit single response

End Application:

Applicable t.O. 15a2-2-14-13 fig 7-1

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Maximum Operating Pressure:

35.0 pounds per square inch single response

Voltage In Volts And Current Type:

115.0 ac

Outside Diameter:

5.500 inches 1st end

Face To Face Distance:

4.060 inches

Bolt Hole Diameter:

0.281 inches 1st end

Bolt Circle Diameter:

4.850 inches 1st end

Flange Face Design:

Plain 1st end

Phase:

Single

Special Features:

Manufacturers suggested name is valve and actuator assembly; all dimensions height 8.94 inch, width 5.53 inch, length 6.91 inch; inlet temp 200 degrees feh max; operating pressure 35 psi; acutator p/n gylg 4912-2, operating voltage 115 vac, 400 cps; motor type single-phase, intermittent duty cycle, rated current 0.6 amps

Frequency In Hertz:

400.0

Material:

Aluminum alloy body

Media For Which Designed:

Air single response

Surface Treatment:

Anodize

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0