

View Online at <https://aerobasegroup.com/nsn/4810-00-585-7135>

**Bolt Hole Quantity:**

12 1st end

**Maximum Operating Temp:**

200.0 degrees fahrenheit single response

**End Application:**

Applicable t.O. 15a2-2-14-13 fig 7-1

**Flange Shape:**

Round with holes 1st end

**Connection Type:**

Flange 1st end

**Maximum Operating Pressure:**

35.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

115.0 ac

**Outside Diameter:**

5.500 inches 1st end

**Face To Face Distance:**

4.060 inches

**Bolt Hole Diameter:**

0.281 inches 1st end

**Bolt Circle Diameter:**

4.850 inches 1st end

**Flange Face Design:**

Plain 1st end

**Phase:**

Single

**Special Features:**

Manufacturers suggested name is valve and actuator assembly; all dimensions height 8.94 inch, width 5.53 inch, length 6.91 inch; inlet temp 200 degrees feh max; operating pressure 35 psi; acutator p/n gylg 4912-2, operating voltage 115 vac, 400 cps; motor type single-phase, intermittent duty cycle, rated current 0.6 amps

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy body

**Media For Which Designed:**

Air single response

**Surface Treatment:**

Anodize

**Style Designator:**

Straight through flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A046b0