## NSN 4810-00-602-1361

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-602-1361

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
0.140
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Vertical
Maximum Operating Pressure:
25.0 pounds per square inch 1st response
Voltage In Volts And Current Type:
120.0 ac and 50.0 dc
120.0 ac and 50.0 dc  Frequency In Hertz:
Frequency In Hertz:
Frequency In Hertz: 50.0 and 60.0
Frequency In Hertz: 50.0 and 60.0 Material:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat Shelf Life:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure: Demilitarization:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure: Demilitarization: No
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Frequency In Hertz: 50.0 and 60.0  Material: Stainless steel seat  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: