# NSN 4810-00-603-8701

Butterfly Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-603-8701

# Maximum Operating Temp:

93.0 degrees fahrenheit single response

# End Application:

Applicable t.O. 15a2-2-13-413 fig 4

# Current Rating In Amps:

1.000

### Flange Shape:

Round 1st end

**Connection Type:** 

Flange 1st end

#### Maximum Operating Pressure:

220.0 pounds per square inch single response

Face To Face Distance:

2.990 inches

Flange Face Design:

Recessed straight 1st end

# **Special Features:**

Manufacturers suggested name is one and one half inch diameter electric air shutoff and modulating valve; operating air pressure 220 psig max; operating air temp 850 degrees feh max; ambient air temp -65 to +200 degrees feh; opening or closing time 10 to 14 sec; actuator motor duty cycle 1 min on, 4 min off; operating voltage 26 vdc; operating current 1 amp at 26 vdc; wt 3.23 lbs

Media For Which Designed:

Air single response

Style Designator:

Straight through flanged ends

**Supplementary Features:** 

Flow control device, steel, mil-ss-5059, class 302

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A046b0