NSN 4810-00-606-2317

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-606-2317

Pipe Size Accommodated:
0.375 inches all ends
Thread Direction:
Right-hand all ends
Aperture Diameter:
0.375 inches
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Current Rating In Amps:
0.054
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Inlet/outlet Operating Pressure Differential:
125.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Voltage In Volts And Current Type:
110.0 ac
Phase:
Single
Frequency In Hertz:
60.0
Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Straight thru
Thread Series Designator:
Npt all ends

NSN 4810-00-606-2317

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0