

View Online at <https://aerobasegroup.com/nsn/4810-00-610-9571>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Gasket sea (boss) 1st end

Current Rating In Amps:

1.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Power Drive Operating Pressure:

3000.0 pounds per square inch

Inlet/outlet Operating Pressure Differential:

50.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

60.0 degrees 1st end

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

2 mtg holes 0.234 in. Id

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0