NSN 4810-00-612-5730

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-612-5730

Thread Direction:

Right-hand all ends

Aperture Diameter:

0.047 inches

Flow Control Device:

Disk

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

0.261

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

200.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Voltage In Volts And Current Type:

115.0 ac

Phase:

Single

Special Features:

Direct acting

Frequency In Hertz:

60.0

Material:

Stainless steel

Media For Which Designed:

Water-oil-gas single response

Surface Treatment:

Chromate zinc

Style Designator:

Angle

NSN 4810-00-612-5730

Solenoid Valve - Page 2 of 2



Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0