## NSN 4810-00-612-5732

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-612-5732

## Thread Direction:

Right-hand all ends

#### Aperture Diameter:

Between 0.062 inches and 0.125 inches

## Flow Control Device:

Disk

#### Flow Control Device Normal Operation Position:

Open

#### **Connection Style:**

Plain, optional en (pipe) all ends

#### **Current Rating In Amps:**

0.261

#### Valve Operation Method:

Solenoid

#### Connection Type:

Threaded internal pipe all ends

#### **Mounting Position:**

Horizontal or vertical

## Inlet/outlet Operating Pressure Differential:

100.0 pounds per square inch

#### Maximum Operating Pressure:

100.0 pounds per square inch single response

#### **Thread Size:**

0.125 inches all ends

#### Voltage In Volts And Current Type:

115.0 ac

#### Phase:

Three

#### Frequency In Hertz:

60.0

## Material:

Stainless steel flow control device

## Media For Which Designed:

Water-oil-gas single response

## Style Designator:

Straight thru

## Thread Series Designator:

Npt all ends

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 4810-00-612-5732

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

