NSN 4810-00-614-6762



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-00-614-6762 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 1.000 inches Flow Control Device: Diaphragm Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:**

0.013

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal

Inlet/outlet Operating Pressure Differential:

125.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

1.000 inches all ends

Voltage In Volts And Current Type:

480.0 ac

Phase:

Single

Special Features:

For general purpose service

Frequency In Hertz:

60.0

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Material Specification:

Astm assn standard single material response body

Media For Which Designed:

Gas, inert 2nd response

Style Designator:

Straight thru

NSN 4810-00-614-6762

Solenoid Valve - Page 2 of 2



Thread Series Designator:
Npt all ends
Furnished Items And Quantity:
1 electrical connector
Shelf Life:
N/a

Unit Of Measure:

Demilitarization: No

Fiig:

A046b0