## NSN 4810-00-623-9975

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Thread Direction:
Right-hand all ends
Aperture Diameter:

Flow Control Device:

0.094 inches

Needle or stem



View Online at https://aerobasegroup.com/nsn/4810-00-623-9975

Closed
Renewable Seat Ring Type:
Pressed-in Pressed-in
Maximum Operating Temp:
77.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Current Rating In Amps:
0.092
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal
Thread Size:
0.250 inches all ends
Voltage In Volts And Current Type:
120.0 ac
Phase:
Single
Frequency In Hertz:
60.0
Material:
Stainless steel flow control device
Surface Treatment:
Paint
Style Designator:
Straight thru
Thread Series Designator:
Npt all ends
Furnished Items And Quantity:
1 electrical connector and 1 nut
Shelf Life:
N/a

## NSN 4810-00-623-9975

Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0