

View Online at <https://aerobasegroup.com/nsn/4810-00-629-2070>

Thread Direction:

Right-hand all ends

Aperture Diameter:

1.000 inches

Flow Control Device:

Diaphragm

Flow Control Device Normal Operation Position:

Open

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Current Rating In Amps:

0.067

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal pipe all ends

Mounting Position:

Horizontal or vertical

Inlet/outlet Operating Pressure Differential:

Between 10.0 pounds per square inch and 125.0 pounds per square inch

Maximum Operating Pressure:

125.0 pounds per square inch single response

Thread Size:

1.000 inches all ends

Voltage In Volts And Current Type:

120.0 ac

Phase:

Single

Special Features:

10.0 psi min operating pressure differential

Frequency In Hertz:

60.0

Material:

Rubber butadiene-acrylonitrile class nbr flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0