NSN 4810-00-670-3493

Solenoid Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-670-3493

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Gasket sea (boss) 1st end

Current Rating In Amps:

2.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss 1st end

Thready Qty Per Inch (tpi):

16 1st end

Inlet/outlet Operating Pressure Differential:

50.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Voltage In Volts And Current Type:

28.0 dc

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Straight thru

Test Data Document:

36659-2-6306 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0