

View Online at <https://aerobasegroup.com/nsn/4810-00-674-1603>

**Maximum Operating Temp:**

570.0 degrees fahrenheit single response

**End Application:**

Applicable t.O. 15a2-2-14-83 fig 6

**Current Rating In Amps:**

0.600

**Valve Operation Method:**

Electric motor or hydraulic

**Flange Shape:**

Round 1st end

**Connection Type:**

Flange 1st end

**Maximum Operating Pressure:**

90.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

26.0 dc

**Flange Face Design:**

Plain 1st end

**Special Features:**

Manufacturers suggested name butterfly valve and actuator; dimensions: length 4.31 inch, width 5.25 inch, height 10.88 inch; 4 inch valve; maximum pressure 90 psig at 570 degrees feg; maximum temp 700 degrees feh; actuator motor p/n dylm 43402-3, motor type split series, explosion proof, continuous duty cycle, rotation reversible, rated load 5.0 lbs, rated current 0.6 amp; actuator p/n cylc6497

**Media For Which Designed:**

Air single response

**Style Designator:**

Straight through y-pattern

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0