NSN 4810-00-676-1139



Solenoid Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4810-00-676-1139 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.250 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 60.0 pounds per square inch **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends Seat Angle: 37.0 degrees all ends **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.562 inches all ends Material: Steel seat **Material Specification:** Mil-s-7720 military specification single material response seat Media For Which Designed: Hydraulic fluid, silicate-ester base single response **Surface Treatment:**

Passivate

Style Designator:

Straight thru

NSN 4810-00-676-1139

Solenoid Valve - Page 2 of 2



Thread Series Designator:
Unjf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

Mil-std (military Standard):

Mil-s-7720 spec.