## NSN 4810-00-695-3284

Solenoid Valve - Page 1 of 2



ononola valvo i ago i ol z
View Online at https://aerobasegroup.com/nsn/4810-00-695-3284
Thread Direction:
Right-hand 1st end
Offset Distance:
0.312 inches
Flow Control Device:
Disk
Flow Control Device Normal Operation Position:
Closed
Bolt Hole Quantity:
6 2nd end
Connection Style:
Plain, optional en (pipe) 1st end
Width:
1.000 inches 2nd end
Length:
2.700 inches 2nd end
Current Rating In Amps:
1.040
Valve Operation Method:
Solenoid
Flange Shape:
Oval with holes 2nd end
Connection Type:
Threaded internal pipe 1st end
Mounting Position:
Horizontal or vertical
Thread Size:
0.125 inches 1st end
Voltage In Volts And Current Type:
12.0 dc
Thickness:
0.290 inches 2nd end
Bolt Hole Diameter:
0.300 inches 2nd end
Bolt Circle Diameter:
1.150 inches 2nd end
Flange Face Design:
Plain 2nd end

**Special Features:** 

W/manual opening device

Material:

Stainless steel flow control device

## NSN 4810-00-695-3284

Solenoid Valve - Page 2 of 2



Style	Design	nator:

Straight through w/offset

**Thread Series Designator:** 

Npt 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0