## NSN 4810-00-706-8004

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-706-8004 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 450.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 2nd end **Current Rating In Amps:** 1.500 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss 2nd end **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 145.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 1st end **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel Media For Which Designed: Air single response **Style Designator:** Straight thru **Thread Series Designator:** Unf 2nd end

Shelf Life:

N/a

## **NSN 4810-00-706-8004** Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A046b0