## NSN 4810-00-712-3739

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-712-3739

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.047 inches
Offset Distance:
1.300 inches
Flow Control Device Normal Operation Position:
Open
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Solenoid
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
16 1st end
Inlet/outlet Operating Pressure Differential:
4.0 pounds per square inch
Maximum Operating Pressure:
750.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Voltage In Volts And Current Type:
14.0 dc and 30.0 dc
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Style Designator:
Caps w/offset
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

## **NSN 4810-00-712-3739** Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A046b0