

View Online at <https://aerobasegroup.com/nsn/4810-00-714-4477>

**Thread Class:**

3b

**End Connection Quantity:**

3

**End Application:**

Applicable t.O. 9h8-14-99-153 fig 6

**Current Rating In Amps:**

0.5

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss

**Features Provided:**

Bulkhead mounted and continuous duty and manual override and spring loaded

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.750 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

160.0 degrees fahrenheit hydraulic fluid, petroleum base

**Voltage In Volts And Current Type:**

17.0 dc and 30.0 dc

**Flow Pattern Quantity:**

3

**Spool Position Quantity:**

2

**Spool Quantity:**

1

**Special Features:**

Manufacturers suggested name valve, 2 position, 3 way - pilot operated, aux. Manual; media fluid mil-h-5606; proof pressure 4500 psig; burst pressure 7500 psig; current 0.5 amps (max) at 24 vdc; 100 psi required to actuate valve; ports per ms33649-8; ambient temp -65 to +160 degrees feh; mounting hole (3) 0.203 to 0.228 inch diameter; wt 1.31 lbs; type of filter oilite bronze; major component parts: solenoid assembly 25350, piston and sleeve assembly 55276, valve cure date parts kit 9672483-10, valve major overhaul parts kit 9672484-10

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**