

View Online at <https://aerobasegroup.com/nsn/4810-00-720-4725>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Offset Distance:

0.530 inches

Flow Control Device:

Poppet

Flow Control Device Normal Operation Position:

Closed

Connection Style:

Plain, optional en (pipe) 1st end

Current Rating In Amps:

75.000

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

20 1st end

Inlet/outlet Operating Pressure Differential:

50.0 pounds per square inch

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Voltage In Volts And Current Type:

124.0 ac and 102.0 ac

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Phase:

Single

Frequency In Hertz:

400.0

Material:

Steel

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Straight through w/offset

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0