NSN 4810-00-720-4725

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-720-4725

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Offset Distance:
0.530 inches
Flow Control Device:
Poppet
Flow Control Device Normal Operation Position:
Closed
Connection Style:
Plain, optional en (pipe) 1st end
Current Rating In Amps:
75.000
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal tube 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Inlet/outlet Operating Pressure Differential:
50.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Voltage In Volts And Current Type:
124.0 ac and 102.0 ac
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Phase:
Single
Frequency In Hertz:
400.0
Material:
Steel
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Straight through w/offset

NSN 4810-00-720-4725

Solenoid Valve - Page 2 of 2



Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A046b0