NSN 4810-00-727-0062

Solenoid Valve - Page 1 of 2

As differentiated by solenoid voltage rating



View Online at https://aerobasegroup.com/nsn/4810-00-727-0062

Pipe Size Accommodated:
0.750 inches all ends
Thread Direction:
Right-hand all ends
Aperture Diameter:
0.750 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Maximum Operating Temp:
212.0 degrees fahrenheit 3rd response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
4 all ends
Maximum Operating Pressure:
300.0 pounds per square inch 4th response
Thread Size:
0.750 inches all ends
Voltage In Volts And Current Type:
115.0 ac
Phase:
Single
Frequency In Hertz:
60.0
Material:
Stainless steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Oil 3rd response
Style Designator:
Straight thru
Thread Series Designator:
Npt all ends
Reference Number Differentiating Characteristics:

NSN 4810-00-727-0062

Solenoid Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0