NSN 4810-00-729-5805

Solenoid Valve - Page 1 of 2

Thread Class: 3b 2nd end

Thread Direction:
Right-hand 1st end
Aperture Diameter:



View Online at https://aerobasegroup.com/nsn/4810-00-729-5805

0.172 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 2nd end
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 2nd end
Maximum Operating Pressure:
Maximum Operating Pressure: 3000.0 pounds per square inch single response
3000.0 pounds per square inch single response
3000.0 pounds per square inch single response Thread Size:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material: Stainless steel flow control device
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material: Stainless steel flow control device Media For Which Designed:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material: Stainless steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material: Stainless steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator:
3000.0 pounds per square inch single response Thread Size: 0.438 inches 2nd end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 22.0 dc and 35.0 dc Outside Diameter Tube Accommodated: 0.250 inches 2nd end Material: Stainless steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator: Err-090

NSN 4810-00-729-5805

Solenoid Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0