NSN 4810-00-729-5805

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-729-5805

Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Aperture Diameter:
0.172 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 2nd end
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Voltage In Volts And Current Type:
22.0 dc and 35.0 dc
Outside Diameter Tube Accommodated:
0.250 inches 2nd end
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Unf 2nd end

NSN 4810-00-729-5805

Solenoid Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

