## NSN 4810-00-732-1321

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-732-1321

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Open
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Current Rating In Amps:
5.500
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
20 1st end  Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 600.0 pounds per square inch single response
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size:
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle:
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type:
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc Outside Diameter Tube Accommodated:
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc Outside Diameter Tube Accommodated: 0.250 inches 1st end
Maximum Operating Pressure:  600.0 pounds per square inch single response Thread Size:  0.437 inches 1st end Seat Angle:  37.0 degrees 1st end Voltage In Volts And Current Type:  12.0 dc Outside Diameter Tube Accommodated:  0.250 inches 1st end Material:
Maximum Operating Pressure:  600.0 pounds per square inch single response  Thread Size:  0.437 inches 1st end  Seat Angle:  37.0 degrees 1st end  Voltage In Volts And Current Type:  12.0 dc  Outside Diameter Tube Accommodated:  0.250 inches 1st end  Material:  Aluminum alloy seat
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc Outside Diameter Tube Accommodated: 0.250 inches 1st end Material: Aluminum alloy seat Media For Which Designed:
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc Outside Diameter Tube Accommodated: 0.250 inches 1st end Material: Aluminum alloy seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response
Maximum Operating Pressure: 600.0 pounds per square inch single response Thread Size: 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Voltage In Volts And Current Type: 12.0 dc Outside Diameter Tube Accommodated: 0.250 inches 1st end Material: Aluminum alloy seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response Style Designator:
Maximum Operating Pressure:  600.0 pounds per square inch single response Thread Size:  0.437 inches 1st end Seat Angle:  37.0 degrees 1st end Voltage In Volts And Current Type:  12.0 dc Outside Diameter Tube Accommodated:  0.250 inches 1st end Material: Aluminum alloy seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response Style Designator: Straight thru

N/a

## NSN 4810-00-732-1321

Solenoid Valve - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0