## NSN 4810-00-739-2604

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-739-2604 **Body Material:** Aluminum alloy mil-a-8097 comp 14s temper t6 **Outside Surface Treatment:** Anodized, mil-a-8625 **Body Style:** Tee Media For Which Designed: Hydrocarbon fuels and oils **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 9/16-18 unif **First End Thread Class:** 3b First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end **Seat Material:** Steel, ams 5610 **Center To Center Distance:** 0.900 inches **Packing Material:** Rubber mil-p-25732 Flow Control Device: Disk, plug type Flow Control Device Material: Steel, ams 5630 **End Connection Quantity:** 3 **Mounting Facility:** Unthd holes **Outlet Pressure Range:** 

+2720.0 to 3260.0 pounds per square inch

**Regulation Type:** 

Automatic single stage

Valve Stem Design:

Single seat

## NSN 4810-00-739-2604

Fluid Pressure Regulating Valve - Page 2 of 2



Valve Loading Method:
Spring
Maximum Inlet Pressure Rating:
4000.0 pounds per square inch
Outlet Pressure Accuracy Rating:
Not rated
Filter:
Not included
Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A21100