## NSN 4810-00-761-6225

Directional Control Linear Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4810-00-761-6225 **End Application:** 9h8-30-117-3 **Valve Operation Method:** Solenoid **Maximum Operating Pressure And Media For Which Designed:** 3000.0 pounds per square inch hydraulic fluid, petroleum base **Criticality Code Justification:** Feat and agav Maximum Operating Tempurature And Media For Which Designed: 160.0 degrees fahrenheit hydraulic fluid, petroleum base **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc Flow Pattern Quantity: **Spool Position Quantity: Spool Quantity:** 2 **Special Features:** Alum alloy body per qq-a-596, alloy 356-t6, anodized per mil-a-8625, solenoid powered, 18 to 30 vdc, 7 amps at 27 vdc, 3000 psi operating pressure, m65 to p160 degrees f operating temp, fluid ports per ms33649-8, media hydraulic oil per mil-h-5606, 3 posn 4 way, used on rh side aft main landing gear control; cognizant service: air force Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A506h0