NSN 4810-00-766-2431

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-766-2431 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.219 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Current Rating In Amps:** 0.230 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Inlet/outlet Operating Pressure Differential:** 250.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single Frequency In Hertz: 60.0 Material: Stainless steel Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator: Straight thru **Thread Series Designator:** Npt all ends

Shelf Life: N/a

NSN 4810-00-766-2431 Solenoid Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A046b0