## NSN 4810-00-781-4731



Solenoid valve - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/4810-00-781-4731	
Pipe Size Accommodated:	
0.125 inches 2nd end	
Thread Class:	
3a 1st end	
Thread Direction:	
Right-hand 1st end	
Aperture Diameter:	
0.010 inches	
Flow Control Device:	
Poppet	
Flow Control Device Normal Operation Position:	
Open	
Maximum Operating Temp:	
165.0 degrees fahrenheit single response	
Connection Style:	
Plain (pipe) 1st end	
Current Rating In Amps:	
0.045	
Valve Operation Method:	
Solenoid	
Connection Type:	
Threaded external tube 1st end	
Mounting Position:	
Horizontal	
Thready Qty Per Inch (tpi):	
27 2nd end	
Maximum Operating Pressure:	
5.0 pounds per square inch single response	
Thread Size:	
0.437 inches 1st end	
Voltage In Volts And Current Type:	
28.0 dc	
Outside Diameter Tube Accommodated:	
0.250 inches 1st end	
Special Features:	

Filterscreen0ninletside

Material:

Stainless steel body

Media For Which Designed:

Air single response

**Surface Treatment:** 

Passivate

## NSN 4810-00-781-4731

Solenoid Valve - Page 2 of 2



Surface	Trootmont	Specification:
ourrace	rreaument	Specification:

Mil-s-5002 military specification single treatment response

**Style Designator:** 

Straight thru

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-5002 spec.