NSN 4810-00-782-1941

Flow Control Device Normal Operation Position:

Solenoid Valve - Page 1 of 2

Thread Class: 3b all ends

Piston

Closed

Thread Direction:
Right-hand all ends
Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4810-00-782-1941

Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Current Rating In Amps:
4.250
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal boss all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 all ends
Maximum Operating Pressure:
50.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Seat Angle:
37.0 degrees all ends
Voltage In Volts And Current Type:
102.0 ac and 124.0 ac
Outside Diameter Tube Accommodated:
0.375 inches all ends
Phase:
Single
Frequency In Hertz:
400.0
Material:
Plastic polytetrafluoroethylene flow control device
Material Specification:
Qq-a-596 federal specification single material response seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response

NSN 4810-00-782-1941

Solenoid Valve - Page 2 of 2



Style Designator:
Straight thru
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0