NSN 4810-00-782-7732

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-782-7732 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.938 inches Flow Control Device: **Poppet** Flow Control Device Normal Operation Position: Closed **Connection Style:** Plain, optional en (pipe) 1st end **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal tube 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Voltage In Volts And Current Type:** 115.0 ac **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Supplementary Features:** Applicable onf5/t38 acft **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4810-00-782-7732

Solenoid Valve - Page 2 of 2



Fiig:

A046b0