

View Online at <https://aerobasegroup.com/nsn/4810-00-795-5039>

**Flow Control Device:**

Piston

**Flow Control Device Normal Operation Position:**

Closed

**Maximum Operating Temp:**

285.0 degrees fahrenheit single response

**End Application:**

Strategic sealift conversion class ships

**Connection Style:**

Socket (tube) all ends

**Current Rating In Amps:**

0.140 and 0.130

**Valve Operation Method:**

Solenoid

**Connection Type:**

Unthreaded internal tube all ends

**Mounting Position:**

Horizontal or vertical

**Inlet/outlet Operating Pressure Differential:**

300.0 pounds per square inch

**Maximum Operating Pressure:**

500.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

208.0 ac and 240.0 ac

**Outside Diameter Tube Accommodated:**

0.500 inches all ends

**Phase:**

Single

**Special Features:**

Solenoid coil not included with valve, uses type am coil only

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Refrigerant 12 1st response

**Style Designator:**

Straight thru

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0