

View Online at <https://aerobasegroup.com/nsn/4810-00-800-0079>

**Pipe Size Accommodated:**

0.500 inches 1st end

**Thread Direction:**

Right-hand 1st end

**Aperture Diameter:**

0.344 inches

**Flow Control Device:**

Poppet

**Flow Control Device Normal Operation Position:**

Open

**Renewable Seat Ring Type:**

Threaded

**Maximum Operating Temp:**

275.0 degrees fahrenheit single response

**End Application:**

Nha p/n's 403340, 403788 (c-130a/133mk); nha 368944 & 368048 (hc-130h); nha 370728, 370718 & 370706 (multiple uses); applicable overhaul kit p/n 6204-1-8

**Connection Style:**

Gasket sea (boss) 1st end

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss 1st end

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Voltage In Volts And Current Type:**

18.0 dc and 30.0 dc

**Special Features:**

Manufacturers suggested name is valve - hydraulic shutoff; applicable fluids mil-h-5606a or mil-h-6083; ambient temps -65 to 275 degrees feh; maximum wt 1.5 lbs; solenoid specification mil-s-4040a; valve specification mil-v-5529a; proof pressure 4500 psi; burst pressure 7500 psi; rated flow 6 gpm; resistance 27 ohms

**Material:**

Stainless steel seat

**Media For Which Designed:**

Hydraulic fluid, mineral base single response

**Surface Treatment:**

Anodize

**Style Designator:**

Straight thru

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0