NSN 4810-00-814-4439

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-814-4439 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.500 inches Flow Control Device: Stem Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 216.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal boss all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 25.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Voltage In Volts And Current Type:** 14.0 dc and 29.0 dc Material: Stainless steel seat **Material Specification:** Qq-a-596, alloy356 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type2 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unjf all ends

Shelf Life: N/a

NSN 4810-00-814-4439

Solenoid Valve - Page 2 of 2



Init	<i>(</i>)+	Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.