

View Online at <https://aerobasegroup.com/nsn/4810-00-818-0440>

Thread Class:

3b

End Connection Quantity:

3

Valve Discharge Flow Rate:

3.0 gallons per minute

End Application:

T.O. 9h8-14-99-83 fig 8

Current Rating In Amps:

1.3

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.375 inches

Body Material:

Aluminum alloy

Criticality Code Justification:

Feat and agav

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

28.0 dc

Flow Pattern Quantity:

3

Spool Position Quantity:

2

Spool Quantity:

1

Special Features:

Manufacturers suggested name valve, position, 3 way, solenoid operated (3000 psi); operating temp range -65 to +160 degrees feh; elec conn ms3102c-msl-4p; wt. 1.6 lbs; all ports per and10050-6 (3/8 tube size); flow capaci type 3 gpm at 75 psi drop est.; operating fluid mil-h-5606; proof pressure 4500 psi

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A506h0