## NSN 4810-00-818-0557

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-818-0557 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.062 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Closed Renewable Seat Ring Type: Threaded **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G10a inverted flar (tube) 1st end **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal tube 1st end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 450.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end Seat Angle: 45.0 degrees 1st end **Voltage In Volts And Current Type: Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Style Designator:** 

Err-090

## NSN 4810-00-818-0557

Solenoid Valve - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf 1st end               |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |

No Fiig: A046b0