## NSN 4810-00-825-4812

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-825-4812

| Pipe Size Accommodated:  |
|--|
| 1.000 inches all ends  |
| Thread Direction:  |
| Right-hand all ends  |
| Aperture Diameter:   |
| 1.000 inches   |
| Flow Control Device:   |
| Piston   |
| Flow Control Device Normal Operation Position:   |
| Closed   |
| Maximum Operating Temp:  |
| 212.0 degrees fahrenheit 2nd response  |
| Connection Style:  |
| G9 plain, optional en (pipe) all ends  |
| Valve Operation Method:  |
| Solenoid   |
| Connection Type:   |
| Threaded internal pipe all ends  |
| Mounting Position:   |
| Horizontal   |
| Thready Qty Per Inch (tpi):  |
| 11-1/2 all ends  |
| Maximum Operating Pressure:  |
| 240.0 pounds per square inch 2nd response  |
| Thread Size:   |
| 1.000 inches all ends  |
| Voltage In Volts And Current Type:   |
| 115.0 ac   |
| Phase:   |
| Single   |
| Frequency In Hertz:  |
| 60.0   |
| Material:  |
| Stainless steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device |
| Media For Which Designed:  |
| Gas, natural 2nd response  |
| Style Designator:  |
| Err-090  |
| Thread Series Designator:  |
| Npt all ends   |
| Reference Number Differentiating Characteristics:  |

As differentiated by solenoid voltage rating

## NSN 4810-00-825-4812

Solenoid Valve - Page 2 of 2



|  |  | ife: |  |
|--|--|------|--|
|  |  |      |  |
|  |  |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0