NSN 4810-00-826-5725

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-826-5725 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.063 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.026 and 0.025 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 125.0 pounds per square inch single response **Thread Size:** 0.125 inches all ends **Voltage In Volts And Current Type:** 230.0 ac and 240.0 ac Phase: Single Frequency In Hertz: 50.0 and 60.0 Material: Copper alloy bodyrubber butadiene-acrylonitrile class nbr flow control device Media For Which Designed: Water-oil-gas single response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends Shelf Life: N/a

Unit Of Measure:

NSN 4810-00-826-5725

Solenoid Valve - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A046b0