NSN 4810-00-833-1600

Fluid Pressure Regulating Valve - Page 1 of 2



١	/iew Online at https://aerobasegroup.com/nsn/4810-00-833-1600
E	Body Material:
ļ	Aluminum alloy qq-a-268, alloy 2024, cond t42
ľ	Media For Which Designed:
ŀ	Hydraulic fluid, petroleum base
F	First End Connection Type:
٦	Threaded internal boss
F	First End Style Designator:
(Gasket seal
F	First End Thread Size And Series/type Designator:
7	7/16-20 unf
F	First End Thread Class:
3	Вь
F	First End Thread Direction:
F	Right-hand
,	Second End Relationship With First End:
1	Not identical
,	Second End Connection Type:
1	Threaded internal boss
5	Second End Style Designator:
(Gasket seal
,	Second End Thread Size And Series/type Designator:
1	1/2-20 unf
,	Second End Thread Class:
3	3b
,	Second End Thread Direction:
F	Right-hand
F	Flow Control Device:
F	Poppet
E	End Connection Quantity:
2	2
(Outlet Pressure Range:
+	+500.0/+600.0 pounds per square inch
F	Regulation Type:
N	Manual single stage
ľ	Manual Control Method:
5	Screw
١	Valve Stem Design:
5	Single seat

Spring

Maximum Inlet Pressure Rating:

1500.0 pounds per square inch

Valve Loading Method:

NSN 4810-00-833-1600

A21100

Fluid Pressure Regulating Valve - Page 2 of 2



Filter:
Not included
Tempurature Rating:
Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: