## NSN 4810-00-837-7504

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-837-7504

| Pipe Size Accommodated:                        |  |  |  |  |
|--|--|--|--|--|
| 0.375 inches 1st end                           |  |  |  |  |
| Thread Direction:                              |  |  |  |  |
| Right-hand 1st end                             |  |  |  |  |
| Aperture Diameter:                             |  |  |  |  |
| 0.188 inches                                   |  |  |  |  |
| Flow Control Device:                           |  |  |  |  |
| Disk   |  |  |  |  |
| Flow Control Device Normal Operation Position: |  |  |  |  |
| Closed   |  |  |  |  |
| Maximum Operating Temp:                        |  |  |  |  |
| 212.0 degrees fahrenheit single response       |  |  |  |  |
| Connection Style:                              |  |  |  |  |
| G9 plain, optional en (pipe) 1st end           |  |  |  |  |
| Current Rating In Amps:                        |  |  |  |  |
| 60.000   |  |  |  |  |
| Valve Operation Method:                        |  |  |  |  |
| Solenoid                                       |  |  |  |  |
| Connection Type:                               |  |  |  |  |
| Threaded internal pipe 1st end                 |  |  |  |  |
| Mounting Position:                             |  |  |  |  |
| Horizontal                                     |  |  |  |  |
| Thready Qty Per Inch (tpi):                    |  |  |  |  |
| 18 1st end                                     |  |  |  |  |
| <b>Maximum Operating Pressure:</b>             |  |  |  |  |
| 175.0 pounds per square inch single response   |  |  |  |  |
| Thread Size:                                   |  |  |  |  |
| 0.375 inches 1st end                           |  |  |  |  |
| Voltage In Volts And Current Type:             |  |  |  |  |
| 110.0 ac                                       |  |  |  |  |
| Phase:   |  |  |  |  |
| Single   |  |  |  |  |
| Frequency In Hertz:                            |  |  |  |  |
| 50.0   |  |  |  |  |
| Material:                                      |  |  |  |  |
| Stainless steel seat                           |  |  |  |  |
| Media For Which Designed:                      |  |  |  |  |
| Water-oil-gas single response                  |  |  |  |  |
| Style Designator:                              |  |  |  |  |
| Err-090  |  |  |  |  |
| Thread Series Designator:                      |  |  |  |  |
| Npt 1st end                                    |  |  |  |  |

## NSN 4810-00-837-7504

Solenoid Valve - Page 2 of 2



| Reference | Number   | Differentiating  | Characteristics:    |
|-----------|----------|------------------|---------------------|
|           | MUIIINEI | Dillelelluatilly | Cital actel istics. |

As differentiated by electrical data

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0