NSN 4810-00-837-7794

Solenoid Valve - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/4810-00-837-7794 **Thread Direction:** Right-hand all ends **Aperture Diameter:** 0.047 inches Flow Control Device: Disk Flow Control Device Normal Operation Position: Open **Maximum Operating Temp:** 200.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.096 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 115.0 ac Phase: Single **Special Features:** Midget-3 way Frequency In Hertz: 60.0 Material: Rubber butadiene-acrylonitrile class nbr flow control device and plastic polyamide flow control device Media For Which Designed: Gas, inert 2nd response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends

NSN 4810-00-837-7794

Solenoid Valve - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A046b0