## NSN 4810-00-846-3357

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-846-3357

Thread Class: 3b all ends Thread Direction: Right-hand all ends Aperture Diameter: 0.500 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp: 160.0 degrees fahrenheit single response
Thread Direction: Right-hand all ends Aperture Diameter: 0.500 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Right-hand all ends Aperture Diameter: 0.500 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Aperture Diameter: 0.500 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
0.500 inches Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Flow Control Device: Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Piston Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Flow Control Device Normal Operation Position: Open Maximum Operating Temp:
Open Maximum Operating Temp:
Maximum Operating Temp:
160.0 degrees fahrenheit single response
5
Connection Style:
G5a flar (tube) all ends
Valve Operation Method:
Solenoid or manual
Connection Type:
Threaded internal tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
25.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Voltage In Volts And Current Type:
18.0 dc and 30.0 dc
Outside Diameter Tube Accommodated:
0.500 inches all ends
Special Features:
Piston flow control with pilot operating device
Material:
Stainless steel flow control device
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

## NSN 4810-00-846-3357

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

