## NSN 4810-00-848-7286

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-848-7286

Pipe Size Accommodated:
0.250 inches all ends
Thread Direction:
Right-hand all ends
Aperture Diameter:
0.188 inches
Flow Control Device:
Piston
Flow Control Device Normal Operation Position:
Closed
Renewable Seat Ring Type:
Pressed-in
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Solenoid
Connection Type:
Threaded internal pipe all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 all ends
Maximum Operating Pressure:
4500.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Voltage In Volts And Current Type:
115.0 ac
Phase:
Single
Special Features:
Designed for hydraulic fluid
Frequency In Hertz:
60.0
Material:
Stainless steel flow control device
Surface Treatment:
Passivate
Style Designator:
Err-090
Thread Series Designator:
Npt all ends

## NSN 4810-00-848-7286

Solenoid Valve - Page 2 of 2



Reference	Number	Differentiating	<b>Characteristics:</b>
11010101100	HUIIDEI	Differentiation	Ullai actel istics.

As differentiated by size of end connections

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0