NSN 4810-00-849-4491

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-849-4491 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Aperture Diameter:** 0.500 inches Offset Distance: 0.810 inches **Flow Control Device: Poppet** Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** G5a flar (tube) 1st end **Current Rating In Amps:** 1.670 **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Voltage In Volts And Current Type:** 18.0 dc and 30.0 dc **Outside Diameter Tube Accommodated:** 0.750 inches 1st end Material: Steel comp 1008 flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize Style Designator: Err-090 **Thread Series Designator:**

Unf 1st end

NSN 4810-00-849-4491

Solenoid Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0