

View Online at <https://aerobasegroup.com/nsn/4810-00-865-2983>

**Bonnet Attachment Method:**

Integral

**Bolt Hole Quantity:**

4 1st end

**Maximum Operating Temp:**

700.0 degrees fahrenheit single response

**End Application:**

T.O. 15e2-2-3-13

**Flange Shape:**

Rectangular with holes 1st end

**Connection Type:**

Flange 1st end

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Voltage In Volts And Current Type:**

24.0 dc

**Face To Face Distance:**

2.475 inches

**Bolt Hole Diameter:**

0.312 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

2.000 inches 1st end

**Center To Center Distance Between Bolt Holes Along Width:**

2.000 inches 1st end

**Flange Face Design:**

Plain 1st end

**Special Features:**

Manufacturers suggested name is motor actuator, butterfly air valve assembly; which consists of the valve and the actuator

**Material:**

Stainless steel body

**Media For Which Designed:**

Air single response

**Surface Treatment:**

Passivate

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A046b0