NSN 4810-00-870-3168

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-870-3168 **Thread Direction:** Right-hand all ends Flow Control Device: Disk Flow Control Device Normal Operation Position: Closed **Maximum Operating Temp:** 85.0 degrees celsius single response **Connection Style:** G9 plain, optional en (pipe) all ends **Current Rating In Amps:** 0.150 **Valve Operation Method:** Solenoid **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Inlet/outlet Operating Pressure Differential:** 200.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Voltage In Volts And Current Type:** 120.0 ac **Center To Center Distance:** 2.562 inches Phase: Single Frequency In Hertz: 60.0 Material: Zinc body Media For Which Designed: Water-oil-gas single response **Thread Series Designator:**

Style Designator: Err-090 Npt all ends Shelf Life: N/a

NSN 4810-00-870-3168 Solenoid Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A046b0