

View Online at <https://aerobasegroup.com/nsn/4810-00-872-0320>

Thread Class:

3b

Valve Discharge Flow Rate:

7.6 gallons per minute

End Application:

Applicable t.O. 9h8-4-168-3 fig 13; u/o code c

Valve Operation Method:

Automatic and solenoid

Connection Type:

Threaded internal boss

Features Provided:

Base mounted

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.750 inches

Criticality Code Justification:

Feat and agav

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

18.0 dc and 30.0 dc

Spool Quantity:

4

Special Features:

Manufacturers suggested name is valve assembly, stablizer flow control; pressures: operating 3000 psig, proof 4500 psig, burst 7500 psig; ports per ms33649-8; ambient temps -65 to +160 degrees feh; coil resistance 47 ohms min; filter element rating 25 micron absolute; dimensions: length 7.7 inches, width 5.2 inches, height 4.8 inches; dry wt 5.5 lbs

Thread Series Designator:

Unjf

Furnished Items And Quantity:

1 lever

Reference Number Differentiating Characteristics:

As differentitaed by source control drawing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A506h0