NSN 4810-00-874-7573

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-874-7573

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Piston

Flow Control Device Normal Operation Position:

Closed

Connection Style:

G42 flared (tube) 1st end

Valve Operation Method:

Solenoid

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

20 1st end

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Voltage In Volts And Current Type:

24.0 dc

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Aluminum alloy seat

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4810-00-874-7573

Solenoid Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

