## NSN 4810-00-880-6093

Solenoid Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4810-00-880-6093
Aperture Diameter:
0.100 inches
Flow Control Device Normal Operation Position:
Closed
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
67.0 degrees fahrenheit single response
Connection Style:
Plain (tube) 1st end
Width:
1.380 inches 2nd end
Length:
1.380 inches 2nd end
Current Rating In Amps:
1.000
Valve Operation Method:
Solenoid
Flange Shape:
Rectangular 2nd end
Connection Type:
Unthreaded internal tube 1st end
Maximum Operating Pressure:
225.0 pounds per square inch single response
Voltage In Volts And Current Type:
23.0 dc and 30.0 dc
Thickness:
0.190 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.062 inches 2nd end
Center To Center Distance Between Bolt Holes Along Width:
1.062 inches 2nd end
Flange Face Design:
Plain 2nd end
Outside Diameter Tube Accommodated:
1.000 inches 1st end
Special Features:
Keyway in electrical receptacle parallel to flow
Media For Which Designed:
Air single response
Style Designator:

Err-090

## NSN 4810-00-880-6093

Solenoid Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0